Blueair by

MODEL BKGM48SL-HC

GLASS DOOR MERCHANDISER

Sleek and durable cooling solution for your food and beverages.





Stainless steel cabinet construction

Stainless steel interior and exterior (galvanized steel back & bottom).



Temperature range between 33°F ~ 39°F

Air guard on rear wall ensures proper air circulation and cooling.



Hydrocarbon refrigerants (R-290)

Increases energy HFC refrigerants. It is safer for the environment and does not cause ozone depletion.



Visual and audible door open alarm

Alarm sounds when doors are not completely closed to protect against food spoilage

Cabinet Dimensions (inches/mm)

L D H
54 3/8" 29 3/4" 81 3/4"
1382 mm 755 mm 2065 mm

Weight (lbs/kg)

Net Weight 580 lbs 263 kg Ship Weight 634 lbs 287 kg

Cabinet construction

- Black or white painted steel exterior and white painted steel interior
- High density foamed in place polyurethane insulation Environmentally safe
- Sturdy, epoxy coated wire shelves with adjustable shelving height
- 4 shelves per compartment.
- Four 4" Diameter swivel casters with front brakes standard.

Refrigeration

- Front slding refrigeration unit allows the unit to be serviced without being moved.
- Self-contained system, bottom mounted compressor provides quick and easy maintenance.
- Epoxy coated evaporator reduces potential corrosion
- Fabric condensation




















Top view

- This product may exprose you to chemicals including Diisononyl Phthalate(DINP), which is known to the State of California to cause cancer. For more information go to www.P65War nings.ca.gov.
 Ce produit peut vous exposer á des agents chimiques incluant le Diisononyl Phthalate(DINP), reconnu par l'Esat de Californie comme causant le cancer, Pour de plus amples renseignements, consulter le site www.P65Warnings.ca.gov.

Doors

- · Sliding door
- Door designed to open easily.
- Double pane glass

Design & Features

- Digital temperature control & monitor system
- Keep food products safe by maintaining constant temperatures
- · Digital display allows for easy monitoring.
- Programs interpet the condition of refrigeration
- · Controls include automatic evaporator fan motor delays

Optional Features & Accessories

- 2.5" diameter casters available
- 6" adjustable legs available
- · Additional shelves are available.

| Doors | 2 |
|----------------------|--|
| Capacity Cu.Ft. | 44.85 |
| Shelves | 8 |
| Refrigerant | R-290 |
| Temperature Range | 33°F ~ 39°F |
| Easy Maintenance | Sliding Condensing Unit |
| Connection | 9.8 ft long (3m) flexible three wire cord with modeled plug |
| Lighting | LED Interior lighting |
| HP | 1/5 HP |
| Voltage | 115V/60Hz |
| Amps | 3.2 |



NEMA 5-15

Blue Air has right to change specifications without further notice.









NEMA Config.